





<b>Product Series :</b>	<b>GSTJ</b>	<b>Brand :</b>	<b>GOTREND</b>
<b>File Version :</b>	<b>GSTJ-SERIES</b>	<b>Editor :</b>	<b>Yinghui Guo</b>
<b>Established Date</b>	<b>2023.08.11</b>	<b>Description :</b>	<b>High Current Inductor</b>
<b>Latest Edit Date :</b>	<b>2024.09.02</b>	<b>Product Type :</b>	<input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

## REMINDERS

- ◆ Product information in this catalog is subject to change without notice, and is for reference only. Therefore, please contact GOTREND Technology to check for the latest information before practical application or usage of the products.
- ◆ This catalog contains only typical specifications, please contact GOTREND Technology for further details if you can not find special components or information you need in this catalogue. Please also approve our product specifications or transact the approval sheet for product specifications before ordering.
- ◆ This catalogue only applies to products purchased through GOTREND Technology or its official agencies. This catalogue does not apply to products that are purchased through other third parties.
- ◆ Please read Attention and CAUTION note (for storage, operating, rating, soldering, mounting and handling) in this catalog to ensure product proper usage.
- ◆ GOTREND Technology is not responsible for issues that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. GOTREND Technology do not grant license of these rights.
- ◆ Information and data provided in the brochure can and do vary in different applications, and actual performance may vary over time.
- ◆ "Delivery Specification" illustrating precautions for the specifications and safety of each product listed in this catalog is available and we strongly recommend to provide these delivery specifications with customers that use these products.
- ◆ For exporting of product in this catalog, please take note it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in accordance to this law.
- ◆ Any reproduction or extraction of the contents in this catalog is prohibited without prior permission from GOTREND Technology.
- ◆ Products listed in this catalog are intended for general electronic device usage under normal operation and use condition including telecommunication equipment, home appliances, sports equipment AV equipment, industrial machine, office equipment etc. Please take note that our products are not designed, intended or authorized for use in below mentioned applications unless explicitly agreed in writing between the parties to avoid product failure that could result in situation where personal injury or death could occur.


- (1) Aerospace/Aviation equipment
- (2) Atomic energy-related equipment
- (3) Disaster prevention/crime prevention equipment
- (4) Electric heating apparatus, burning equipment
- (5) Medical equipment
- (6) Military equipment
- (7) Power-generation control equipment
- (8) Public information-processing equipment
- (9) Safety equipment
- (10) Seabed equipment
- (11) Transportation control equipment
- (12) Transportation equipment (cars, electric trains, ships, etc.)
- (13) Other applications that are not considered general-purpose applications

- ◆ Our manufacturing sites fully compliance with requirement regarding the quality management system in the automotive industry under the IATF 16949 standard. GOTREND Technology respect individual agreements with reference to customer requirements and customer specific requirements (CSR). We will like to emphasize that only requirements mutually agreed upon will in implemented in our Quality Management System taking into consideration that IATF 16949 may appear to support the acceptance of unilateral requirements. We will only legally bind to this individually agreed upon agreement under the IATF 16949 standard.
- ◆ The product itself is a powder metallurgy product, so the structure is relatively fragile, and it should not be used for products that are easy to fall. In addition, when this product is assembled, it should avoid collision with the tool or mechanism shell. 
- ◆ It is not recommended to use hot air gun for disassembling of this product. When using of hot air gun to repair other parts, please also take note that long time or high temperature exposure of this product will also damage the inductance device. If you need to use the hot air gun to disassemble the product, it is recommended to adjust the hot air gun temperature to 380 deg.C±5 deg.C. The blower head of the hot air gun should be perpendicular and at least 1cm away from the product. After heating the product to the tin material melting point, use tweezers to remove the product from the PCB. 

<b>Product Series :</b>	<b>GSTJ</b>	<b>Brand :</b>	<b>GOTREND</b>
<b>File Version :</b>	<b>GSTJ-SERIES</b>	<b>Editor :</b>	<b>Yinghui Guo</b>
<b>Established Date</b>	<b>2023.08.11</b>	<b>Description :</b>	<b>High Current Inductor</b>
<b>Latest Edit Date :</b>	<b>2024.09.02</b>	<b>Product Type :</b>	<input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

**Features & Application :**

- \* Compact design.
- \* High current , low DCR , high efficiency.
- \* Very low acoustic noise and very low leakage flux noise.
- \* High reliability.
- \* 100% Lead ( Pb ) - Free and RoHS compliant.
- \* Note PC power system , incl. IMVP-6 , DC / DC converter.



( Picture for reference only )

**Part No. Example :**

PN	:	<b>GSTJ</b>	<b>1580</b>	<b>P</b>	<b>A</b>	<b>-</b>	<b>1R0</b>	<b>M</b>
-----		-----	-----	---	---		-----	---
ID	:	1	2	3	4		5	6
1	:	GOTREND Series : GSTJ						
2	:	Type Size Code : 1580 = 15.5 x 14.7 x 8.0 mm						
3	:	P = Pb free < 1000 ppm						
4	:	[ A ] : Alloy Powde , [ C ] : Carbonyl Iron Powder						
5	:	Inductance : 1R0 = 1.0 uH						
5	:	Tolerance : M = +/-20%						


**Basic Information :**

<b>Made in</b>	China
<b>Pin Foot</b>	SMD
<b>Shielding</b>	Yes
<b>J-STD-020</b>	MSL Level 1
<b>RoHS</b>	Compliant
<b>REACH</b>	Compliant
<b>Halogen</b>	Free

**Operating & Storage Condition :**

- \* Operating Temp    -55 ~ +125 °C ( Including self - temperature rise )
- \* Storage Temp        1. -10 ~ +45 °C , 50 ~ 60% RH ( Product with taping )  
                              2. -55 ~ +125 °C ( On board )
- \* Storage Life Time    6 Month ( Less than 40 °C and 60% RH )

**Attention & Caution :**


- \* Keep out of            Splashing water or salt water
- \* Avoid                    Toxic Gas (Hydrogen sulfide, Sulfurous acid, Chlorine, Ammonia)
-  Vibrations or shocks which exceed the specified condition
- Dew condense
- Layout near the edge of PCB
- Over flexure after SMT mounting & PCBA
- \* Pin foot or SMD pad solderability: Pb free type is best within 6 months after delivery
- \* Humidity sensitive , IPC/JEDEC J-STD-020 MSL if over Level 1, recommend bake 30mins@150 degree before PCBA
- \* Caution for human life relative applications : PLS contact & consult with GOTREND team in design stage.

**Test Condition :**

- \* Equipment            HP4284A , HP42841A - L , Q , DCR , IDC  
                              HP8753D Network analyzer - SRF
- \* Standard Atmosphere Conditions:  
    Ambient            Temperature 20 ± 15 °C  
                              Humidity RH 65 ± 20%
- \* If there may be any doubt on the test result ,  
    Measurement shall be made within the following limits:  
    Ambient            Temperature 25 ± 5 °C  
                              Humidity RH 75 ± 10%

**Recommend IR Reflow Curve : GTX-IR-FILE001**

Lead Free Solder : A = 217 deg.C , B = 245+/-5 deg.C  
Time : C = 40 ~ 60 Sec.



Notice : Iron Soldering , Solder < 30 Watt ,  
Direct touch the terminal x 3 Sec. Max. @ 350 deg.C

<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date :</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize


#### High Current Inductor - GSTJ Series Type

Part Name	L ( mm ) Typ.	W ( mm ) Typ.	H ( mm ) Max.	Inductance Range ( uH ) M=+/-20%	DCR ( m Ohm ) Typ.	I <sub>rms</sub> ( A ) Typ.	I <sub>sat</sub> ( A ) Typ.	Page
GSTJ8045PC	8.7	8.1	5.0	0.22 ~ 47.00	0.7 ~ 225.0	2.5 ~ 45.0	2.8 ~ 50.0	5
GSTJ107050PC	10.0	7.0	5.0	0.15 ~ 10.00	0.6 ~ 34.8	7.0 ~ 55.0	9.5 ~ 65.0	6
GSTJ117040PA	11.2	7.2	4.0	0.15 ~ 10.00	0.75 ~ 48.5	5.5 ~ 48.0	7.50 ~ 65.0	7
GSTJ117050PA	11.2	7.2	5.0	0.15 ~ 10.00	0.98 ~ 39.0	6.0 ~ 36.0	9.0 ~ 70.0	8
GSTJ118050PA	11.2	7.8	5.0	0.15 ~ 10.00	0.6 ~ 34.0	6.5 ~ 48.0	9.5 ~ 76.0	9
GSTJ118050PC	11.2	7.8	5.0	0.15 ~ 15.00	0.75 ~ 50.0	5.5 ~ 50.0	8.5 ~ 80.0	10
GSTJ128030PC	12.8	8.0	3.0	0.22 ~ 10.00	0.9 ~ 58	5.0 ~ 42.0	7.5 ~ 47.0	11
GSTJ128040PC	12.8	8.0	4.0	0.22 ~ 10.00	0.52 ~ 38.5	6.0 ~ 60.0	8.5 ~ 65.0	12
GSTJ128050PC	12.8	8.0	4.8	0.22 ~ 10.00	0.45 ~ 27.2	7.5 ~ 60.0	9.5 ~ 84.0	13
GSTJ1580PC	15.5	14.7	8.0	1.00 ~ 68.0	1.65 ~ 68.0	5.0 ~ 29.0	9.0 ~ 56.0	14
GSTJ1770PA	18.5	17.3	7.0	1.00 ~ 100.00	1.65 ~ 110.0	4.0 ~ 32.0	9.0 ~ 90.0	15

<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ8045PC-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.4)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
8.7	8.1	5.0	1.8	3.0	9.6	3.9	3.5

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm)		I <sub>rms</sub> (A)		I <sub>sat</sub> (A)	
			Typ	Max	Typ	Max	Typ	Max
GSTJ8045PC-R22M	0.22	M	0.7	0.8	44.0	45.0	50.0	49.0
GSTJ8045PC-R33M	0.33	M	2.0	2.4	32.0	30.0	45.0	40.0
GSTJ8045PC-R47M	0.47	M	2.8	3.0	28.0	25.0	42.0	38.0
GSTJ8045PC-R56M	0.56	M	3.2	3.5	24.0	23.0	26.0	25.0
GSTJ8045PC-R68M	0.68	M	3.8	4.0	23.0	22.0	24.0	23.0
GSTJ8045PC-R82M	0.82	M	4.4	5.0	21.0	20.0	22.0	21.0
GSTJ8045PC-1R0M	1.00	M	4.6	5.0	16.0	15.0	22.0	20.0
GSTJ8045PC-1R5M	1.50	M	7.6	7.9	15.0	14.0	21.0	19.0
GSTJ8045PC-2R2M	2.20	M	12.8	13.0	13.0	12.0	15.0	14.0
GSTJ8045PC-3R3M	3.30	M	9.0	10.0	15.0	13.0	15.5	14.5
GSTJ8045PC-4R7M	4.70	M	17.0	18.0	10.5	9.5	16.0	15.0
GSTJ8045PC-6R8M	6.80	M	30.0	32.0	8.0	7.0	10.0	9.0
GSTJ8045PC-100M	10.00	M	52.0	53.0	5.5	5.0	16.0	15.0
GSTJ8045PC-150M	15.00	M	64.0	66.0	5.0	4.5	15.0	14.0
GSTJ8045PC-220M	22.00	M	103.0	105.0	4.0	3.8	13.0	12.5
GSTJ8045PC-330M	33.00	M	156.0	158.0	3.5	3.0	3.8	3.5
GSTJ8045PC-470M	47.00	M	220.0	225.0	2.9	2.5	3.1	2.8

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%


\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C

\* I<sub>sat</sub> : DC current (A) that will caus Lo to drop approximately 30%

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ107050PC-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
10.0	7.0	5.0	2.5	2.5	11.5	5.5	3.5

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm) (Max.)	I <sub>rms</sub> (A) (Typ.)	I <sub>sat</sub> (A) (Typ.)
GSTJ107050PC-R15M	0.15	M	0.60	55.00	65.00
GSTJ107050PC-R20M	0.20	M	0.65	45.00	75.00
GSTJ107050PC-R22M	0.22	M	0.75	44.00	76.00
GSTJ107050PC-R33M	0.33	M	0.80	38.00	55.00
GSTJ107050PC-R47M	0.47	M	1.20	35.00	45.00
GSTJ107050PC-3R3M	3.30	M	11.00	13.00	13.50
GSTJ107050PC-100M	10.00	M	34.80	7.00	9.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ117040PA-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
11.2	7.2	4.0	2.5	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm) (Max.)	I <sub>rms</sub> (A) (Typ.)	I <sub>sat</sub> (A) (Typ.)
GSTJ117040PA-R15M	0.15	M	0.75	48.00	65.00
GSTJ117040PA-R22M	0.22	M	1.20	32.00	55.00
GSTJ117040PA-R27M	0.27	M	1.44	25.00	45.00
GSTJ117040PA-R33M	0.33	M	1.80	20.00	40.00
GSTJ117040PA-R47M	0.47	M	2.10	18.00	35.00
GSTJ117040PA-3R3M	3.30	M	17.00	9.50	10.00
GSTJ117040PA-100M	10.00	M	48.50	5.50	7.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ117050PA-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
11.2	7.2	5.0	2.5	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm) (Max.)	I <sub>rms</sub> (A) (Typ.)	I <sub>sat</sub> (A) (Typ.)
GSTJ117050PA-R15M	0.15	M	0.98	36.00	70.00
GSTJ117050PA-R22M	0.22	M	0.88	50.00	68.00
GSTJ117050PA-R27M	0.27	M	1.10	36.00	62.00
GSTJ117050PA-R30M	0.30	M	1.10	34.00	58.00
GSTJ117050PA-R33M	0.33	M	1.10	32.00	50.00
GSTJ117050PA-R47M	0.47	M	1.50	30.00	40.00
GSTJ117050PA-R82M	0.82	M	3.00	18.00	20.00
GSTJ117050PA-1R0M	1.00	M	3.20	15.00	18.00
GSTJ117050PA-3R3M	3.30	M	15.80	11.50	11.50
GSTJ117050PA-100M	10.00	M	39.00	6.00	9.00

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C

\* I<sub>sat</sub> : DC current (A) that will caus Lo to drop approximately 30%


\* The part temperature (ambient + temp rise ) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.



Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ118050PA-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
11.2	7.8	5.0	3.0	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance ( uH )	Inductance Tolerance	DCR ( m Ohm ) ( Max. )	I <sub>rms</sub> ( A ) ( Typ. )	I <sub>sat</sub> ( A ) ( Typ. )
GSTJ118050PA-R15M	0.15	M	0.60	48.00	76.00
GSTJ118050PA-R22M	0.22	M	0.76	45.50	75.00
GSTJ118050PA-3R3M	3.30	M	10.50	12.00	12.50
GSTJ118050PA-100M	10.00	M	34.00	6.50	9.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ118050PC-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(Max.)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
11.2	7.8	5.0	3.0	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance ( uH )	Inductance Tolerance	DCR ( m Ohm ) ( Max. )	I <sub>rms</sub> ( A ) ( Typ. )	I <sub>sat</sub> ( A ) ( Typ. )
GSTJ118050PC-R15M	0.15	M	0.75	50.00	80.00
GSTJ118050PC-R22M	0.22	M	0.53	57.00	70.00
GSTJ118050PC-R33M	0.33	M	0.90	35.00	65.00
GSTJ118050PC-R47M	0.47	M	1.00	30.00	60.00
GSTJ118050PC-R68M	0.68	M	1.80	28.00	45.00
GSTJ118050PC-3R3M	3.30	M	8.10	10.50	10.50
GSTJ118050PC-100M	10.00	M	29.70	7.50	9.00
GSTJ118050PC-150M	15.00	M	50.00	5.50	8.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C

\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ128030PC-SERIES

Dimension [ mm ] :


Top View

Side View

Bottom View

Recommend PCB Layout

Schematic



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(+/-0.2)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
12.8	8.0	2.8	3.0	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm) (Max.)	I <sub>rms</sub> (A) (Typ.)	I <sub>sat</sub> (A) (Typ.)
GSTJ128030PC-R22M	0.22	M	0.90	42.00	47.00
GSTJ128030PC-R33M	0.33	M	1.60	30.00	55.00
GSTJ128030PC-R47M	0.47	M	1.90	28.00	47.00
GSTJ128030PC-3R3M	3.30	M	15.00	10.50	13.50
GSTJ128030PC-100M	10.00	M	58.00	5.00	7.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ128040PC-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(+/-0.2)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
12.8	8.0	3.8	3.0	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm) (Max.)	I <sub>rms</sub> (A) (Typ.)	I <sub>sat</sub> (A) (Typ.)
GSTJ128040PC-R22M	0.22	M	0.52	60.00	65.00
GSTJ128040PC-R47M	0.47	M	1.60	30.00	55.00
GSTJ128040PC-R56M	0.56	M	2.00	28.00	50.00
GSTJ128040PC-R68M	0.68	M	3.00	20.00	40.00
GSTJ128040PC-3R3M	3.30	M	10.95	11.50	12.50
GSTJ128040PC-100M	10.00	M	38.50	6.00	8.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worse case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Product Series : GSTJ	Brand : GOTREND
File Version : GSTJ-SERIES	Editor : Yinghui Guo
Established Date : 2023.08.11	Description : High Current Inductor
Latest Edit Date : 2024.09.02	Product Type : <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

### GSTJ128050PC-SERIES

Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.4)	C(+/-0.2)	D(+/-0.5)	E(+/-0.5)	F(Ref.)	G(Ref.)	H(Ref.)
12.8	8.0	4.8	3.0	2.5	12.5	5.0	5.0

Electrical Characteristics :

Part No.	Inductance ( uH )	Inductance Tolerance	DCR ( m Ohm ) ( Max. )	I <sub>rms</sub> ( A ) ( Typ. )	I <sub>sat</sub> ( A ) ( Typ. )
GSTJ128050PC-R22M	0.22	M	0.45	60.00	84.00
GSTJ128050PC-R33M	0.33	M	0.90	43.00	75.00
GSTJ128050PC-R47M	0.47	M	1.00	35.00	60.00
GSTJ128050PC-R56M	0.56	M	1.80	28.00	50.00
GSTJ128050PC-1R0M	1.00	M	3.00	22.00	40.00
GSTJ128050PC-3R3M	3.30	M	9.10	12.00	12.00
GSTJ128050PC-100M	10.00	M	27.20	7.50	9.50

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C


\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

\* The part temperature (ambient + temp rise) : should not exceed 125°C under worst case operating conditions. Circuit design component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

## GSTJ1580PC-SERIES

### Dimension [ mm ] :



Marking : Inductance code

A(+/-0.5)	B(+/-0.2)	C(Max.)	D(+/-0.5)	E(+/-0.2)	F(Ref.)	G(Ref.)	H(Ref.)
15.5	14.7	8.0	2.5	8.0	15.8	8.9	8.5

### Electrical Characteristics :

Part No.	Inductance (uH)	Inductance Tolerance	DCR (m Ohm)		I <sub>rms</sub> (A)		I <sub>sat</sub> (A)	
			Typ	Max	Typ	Max	Typ	Max
GSTJ1580PC-1R0M	1.00	M	1.65	1.80	29.00	27.50	56.00	54.00
GSTJ1580PC-1R5M	1.50	M	2.40	2.65	25.50	24.50	37.50	36.50
GSTJ1580PC-2R2M	2.20	M	2.50	2.80	24.00	22.50	42.00	40.00
GSTJ1580PC-3R3M	3.30	M	3.30	3.60	22.00	21.00	36.00	34.00
GSTJ1580PC-4R7M	4.70	M	4.50	5.00	19.00	17.50	34.00	32.00
GSTJ1580PC-6R8M	6.80	M	6.50	7.00	16.00	14.50	32.00	30.00
GSTJ1580PC-100M	10.00	M	11.00	13.00	13.00	11.50	30.00	27.00
GSTJ1580PC-150M	15.00	M	13.50	15.00	11.00	10.00	19.00	17.00
GSTJ1580PC-220M	22.00	M	24.00	26.00	9.00	8.50	14.00	12.00
GSTJ1580PC-330M	33.00	M	30.00	35.00	8.00	7.50	12.00	11.00
GSTJ1580PC-470M	47.00	M	40.00	42.00	6.50	6.00	12.00	10.00
GSTJ1580PC-680M	68.00	M	62.00	68.00	5.50	5.00	10.00	9.00

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%


\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C

\* I<sub>sat</sub> : DC current (A) that will caus Lo to drop approximately 30%

<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

## GSTJ1770PC-SERIES

**Dimension [ mm ] :**



**Marking : Inductance code**

A(Max.)	B(Max.)	C(Max.)	D(+/-0.5)	E(+/-0.3)	F(Ref.)	G(Ref.)	H(Ref.)
18.5	17.3	7.0	2.7	12.0	18.5	11.7	12.2

**Electrical Characteristics :**

Part No.	Inductance (uH)	Inductance Tolerance	DCR ( m Ohm )		I <sub>rms</sub> ( A )		I <sub>sat</sub> ( A )	
			Typ	Max	Typ	Max	Typ	Max
GSTJ1770PC-1R0M	1.00	M	1.65	1.80	32.00	30.00	90.00	88.00
GSTJ1770PC-1R5M	1.50	M	2.00	2.30	30.00	28.00	57.00	55.00
GSTJ1770PC-2R2M	2.20	M	2.25	2.50	29.00	27.00	55.00	53.00
GSTJ1770PC-3R3M	3.30	M	3.20	3.60	25.00	23.00	45.00	43.00
GSTJ1770PC-4R7M	4.70	M	3.35	4.70	22.00	20.00	40.00	38.00
GSTJ1770PC-6R8M	6.80	M	7.50	7.80	19.00	17.00	32.00	30.00
GSTJ1770PC-100M	10.00	M	10.80	12.00	16.50	14.50	25.00	23.00
GSTJ1770PC-220M	22.00	M	20.90	23.00	10.00	9.00	18.00	16.00
GSTJ1770PC-330M	33.00	M	33.50	37.00	7.50	6.50	20.00	18.00
GSTJ1770PC-470M	47.00	M	45.50	50.00	6.00	5.00	13.00	11.00
GSTJ1770PC-680M	68.00	M	62.80	69.00	5.50	4.50	11.00	9.00
GSTJ1770PC-101M	100.00	M	100.00	110.00	4.50	4.00	10.00	9.00

\* Test Condition : @100KHz , 1.0Vrms , 25°C Ambient

\* Inductance Tolerance : M = +/-20%

\* I<sub>rms</sub> : DC current (A) that will cause an approximately 40°C

\* I<sub>sat</sub> : DC current (A) that will cause L<sub>o</sub> to drop approximately 30%

<b>Product Series :</b>	<b>GSTJ</b>	<b>Brand :</b>	<b>GOTREND</b>
<b>File Version :</b>	<b>GSTJ-SERIES</b>	<b>Editor :</b>	<b>Yinghui Guo</b>
<b>Established Date</b>	<b>2023.08.11</b>	<b>Description :</b>	<b>High Current Inductor</b>
<b>Latest Edit Date :</b>	<b>2024.09.02</b>	<b>Product Type :</b>	<input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

#### Care note :

Care note for Use :

(1) Storage Condition :

Temperature 25 to 35 °C , Humidity 45 to 60% RH

(2) Use Temperature :

- a. Minimum Temperature : -55 °C Ambient temperature of this product.
- b. Maximum Temperature : +125 °C The value of temperature including ambient and temperature rise of this product.
- c. Reliability test temperature range from -55 ~ +125 °C
- d. However, this is not meant as temperature grade guarantee for UL.

(3) Model :

When this product was used in a similar or as new product to the original one, sometimes it might be unable to satisfy the specifications due to difference in condition of usage.

(4) Drop :

If this product suffered mechanical stress such as drop, characteristics may become poor ( due to damage on coil / bobbin / ferrite ... etc. )

Never use such stressed product.

Care note for Safety :

(1) Provision to Abnormal Condition :

This product itself does not have any protective function in abnormal condition such as overload, short-circuit and open-circuit conditions, etc.

Therefore, it shall be confirmed from the end product that there is no risk of smoking, fire, dielectric withstand voltage insulation resistance, etc. in abnormal conditions to provide protective devices and /or protection circuit in the end product.

(2) Temperature Rise :

Temperature rise on this product depends on the installation condition on end products.

It shall be confirmed on the actual end product that temperature rise of this product is within the specified temperature class limit.

(3) Dielectric Strength :

Dielectric withstanding test with higher voltage than specific value will damage insulating material and shorten its life.

(4) Water :

This product must not be used in wet condition resulted from water, coffee or any liquid contact because insulation strength becomes very low under such condition.

(5) Potting :

If this product is potted in some compound, coating material of magnet wire might be occasionally damaged. Please ask us if you intend to pot this product.




(6) Detergent :

Please consult our company immediately once under such circumstances because product reliability confirmation etc. is needed when this product come in contact with these chemicals.



<b>Product Series :</b> GSTJ	<b>Brand :</b> GOTREND
<b>File Version :</b> GSTJ-SERIES	<b>Editor :</b> Yinghui Guo
<b>Established Date</b> 2023.08.11	<b>Description :</b> High Current Inductor
<b>Latest Edit Date :</b> 2024.09.02	<b>Product Type :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Customize

**Reliability :**


SN	Test Item	Test Condition	Specification		
1	<b>Dimension</b>	Actual Size ...	Meet Spec		
2	<b>Thermal Shock (Temperature Cycle)</b>	Temperature : -55 ~ +125 °C kept stabilized for 30 min. each Cycle : 100 Cycles ( power off )	Elec. no variation Appearance no deformation		
3	<b>Humidity Resistance</b>	Humidity : 90% ~ 95% RH Temperature : 60 ± 2 °C, Test Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation		
4	<b>HighTemperature</b>	Temperature : 155 ± 2 °C Testing Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation		
5	<b>Low Temperature</b>	Temperature : -55 ± 2 °C Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation		
6	<b>Temperature and Humidity Cycle</b>	Temperature	Humidity	Time	Elec. no variation Appearance no deformation
		25 °C	90% ~ 95% RH	3.0 Hr	
		55 °C	95% ~ 96% RH	5.0 Hr	
		25 °C	90% ~ 95% RH	3.0 Hr	
		Cycle : 20 Cycles			
7	<b>Vibration</b>	Frequency : 10Hz ~ 55Hz, Amplitude : 1.5 mm Direction : X, Y, Z, Time : 2 Hours each	Elec. no variation Appearance no deformation		
8	<b>Solderability</b>	Go through real SMT IR-Reflow .... The profile like our suggest profile. Preheat : 160 ± 10 °C ( 90 sec ) Peak : 245 ± 5 °C Peak Time : 50 Sec. / up 217 °C	Elec. no variation Appearance no deformation		
9	<b>Soldering Heat Resistance</b>	Preheat : 160 ± 10 °C ( 90 sec ) Solder : Sn / Ag / Cu ( Pb Free ) Solder Temp. : 260 ± 5 °C, Time : 3 ± 1 seconds	Elec. no variation Appearance no deformation		
10	<b>Iron Solder Heat Resistance</b>	Solder Temp. : 350 ± 5 °C Flux : Rosin, Time : 3 ± 1 seconds	Elec. no variation Appearance no deformation		
11	<b>Bending Strength</b>	Unit : mm  Force : 1Kg / min.	Elec. no variation Appearance no deformation		
12	<b>Flexure Strength</b>	Unit : mm  Solder cream 0.15 mm	Elec. no variation Appearance no deformation		
13	<b>Terminal Strength</b>	 Mount on PCB Solder Cream 0.15 mm Push 10N force to X, Y direction	Elec. no variation Appearance no deformation		
14	<b>Load life</b>	Temperature : 25 ± 3 °C Load : Allowed DC Current, Test Time : 96 ± 2 Hours	Elec. no variation Appearance no deformation		

**Product Series :** GSTJ  
**File Version :** GSTJ-SERIES  
**Established Date** 2023.08.11  
**Latest Edit Date :** 2024.09.02

**Brand :** GOTREND  
**Editor :** Yinghui Guo  
**Description :** High Current Inductor  
**Product Type :**  Standard  Customize


**Packaging Information :**

Tape Dimension ( mm )



SIZE/mm	W	P	A0	B0	K0	T	F
8045P	16.0	12.0	8.10	8.70	4.80	0.35	7.50
107050P	24.0	12.0	7.30	10.40	5.30	0.40	11.50
117040P	24.0	12.0	7.30	11.70	4.30	0.40	11.50
117050P	24.0	12.0	7.30	11.70	5.30	0.40	11.50
118050PA	24.0	12.0	8.30	11.70	5.10	0.40	11.50
118050PC	24.0	12.0	8.30	11.70	5.10	0.40	11.50
128030P	24.0	12.0	8.10	12.70	3.30	0.40	11.50
128040P	24.0	12.0	8.10	12.70	4.30	0.40	11.50
128050P	24.0	12.0	8.10	12.70	5.30	0.40	11.50
1580P	24.0	20.0	15.20	16.00	8.50	0.50	13.20
1770P	32.0	24.0	17.50	18.50	7.50	0.50	14.20

Reel Dimension ( mm )




SIZE/mm	Reel Size	A	B	C	D	QTY / Reel
8045P	13" × 16 mm	330	100	13.0	16.8	800 PCS
107050P	13" × 24 mm	330	100	13.5	24.0	800 PCS
117040P	13" × 24 mm	330	100	13.5	24.0	1,000 PCS
117050P	13" × 24 mm	330	100	13.5	24.0	800 PCS
118050PA	13" × 24 mm	330	100	13.5	24.0	800 PCS
118050PC	13" × 24 mm	330	100	13.5	24.0	800 PCS
128030P	13" × 24 mm	330	100	13.5	24.0	1,000 PCS
128040P	13" × 24 mm	330	100	13.5	24.0	1,000 PCS
128050P	13" × 24 mm	330	100	13.5	24.0	800 PCS
1580P	13" × 24 mm	330	100	13.5	24.0	300 PCS
1770P	13" × 32 mm	330	100	13.5	32.0	300 PCS

**Product Series :** GSTJ  
**File Version :** GSTJ-SERIES  
**Established Date** 2023.08.11  
**Latest Edit Date :** 2024.09.02

**Brand :** GOTREND  
**Editor :** Yinghui Guo  
**Description :** High Current Inductor  
**Product Type :**  Standard  Customize

**Packaging Information :**


Tearing Off Force




The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions (referenced ANSI / EIA - 481 - D - 2008 of 4.11 standard).

Room Temp. (°C)	Room Humidity (%)	Room Atm. (hPa)	Tearing Speed (mm / min)
5 ~ 35	45 ~ 85	860 ~ 1060	300

Box Package



**13" Small Box**



**13" Large Box**

SIZE/mm	Reels size	A	B	C	Large Box	D	E	F	Reels in Small Box (QTY)	Small Box in Large Box(QTY)
8045P	13"	335	335	23	13"	350	350	220	1(800)	7(5,600)
107050P	13"	335	335	40	13"	350	350	220	1(800)	5(4,000)
117040P	13"	335	335	40	13"	350	350	220	1(1,000)	5(5,000)
117050P	13"	335	335	40	13"	350	350	220	1(800)	5(4,000)
118050PA	13"	335	335	40	13"	350	350	220	1(800)	5(4,000)
118050PC	13"	335	335	40	13"	350	350	220	1(800)	5(4,000)
128030P	13"	335	335	40	13"	350	350	220	1(1,000)	5(5,000)
128040P	13"	335	335	40	13"	350	350	220	1(1,000)	5(5,000)
128050P	13"	335	335	40	13"	350	350	220	1(800)	5(4,000)
1580P	13"	335	335	40	13"	350	350	220	1(300)	5(1,500)
1770P	13"	340	340	54	13"	350	350	245	1(300)	4(1,200)